

60A, 1000V Standard Rectifier

Description


The AKD60100NCS is a Standard Rectifier. It's a SIPOS+GPP double passivation chip, with high reliability. It has low leakage current and low forward voltage drop, Improved thermal behaviour.

Features

- Typical Forward Voltage: $V_F=1.05V @ I_F=60A$
- Reverse Voltage: $V_{RRM}=1000V$
- Avalanche Energy Rated
- SIPOS+GPP double passivation

Applications

- Diode for main rectification
- For single and three phase
- Bridge configurations



Absolute Maximum Ratings per diode at $T_C=25^\circ C$ unless otherwise noted

Symbol	Parameter		Ratings	Unit	
V_{RRM}	Peak Repetitive Reverse Voltage		1000	V	
V_{RWM}	Working Peak Reverse Voltage		1000	V	
V_R	DC Blocking Voltage		1000	V	
$I_{F(AV)}$	Average Rectified Forward Current	per device at $T_C=120^\circ C$	60	A	
I_{FSM}	Non-repetitive Peak Surge Current	$t = 10 \text{ ms}$ (50 Hz), sine	$T_{VJ}=45^\circ C$ $V_R = 0 \text{ V}$	720	
			$T_{VJ}=150^\circ C$ $V_R = 0 \text{ V}$	540	
I^2t	value for fusing	$t = 10 \text{ ms}$ (50 Hz), sine	$T_{VJ}=45^\circ C$ $V_R = 0 \text{ V}$	2592	
			$T_{VJ}=150^\circ C$ $V_R = 0 \text{ V}$	1458	
T_J	Operating Junction Temperature Range		-40~+150	°C	
T_{STG}	Storage Temperature Range		-40~+150	°C	

Thermal Characteristics

Symbol	Parameter	Ratings	Unit
R_{th} (J-C)	Thermal Resistance, Junction to case	0.49	°C/W

Electrical Characteristics per diode @ $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V_F	Forward Voltage Drop	$I_F=60\text{A}$	-	1.05	1.4	V
		$I_F=60\text{A}, T_c=120^\circ\text{C}$	-	0.95	1.2	V
I_R	Reverse Leakage Current	$V_R=1000\text{V}$	-	-	1	mA

Typical Performance Characteristics

Fig. 1. Typical Characteristics: V_F vs. I_F




Fig. 2. Typical Characteristics: V_R vs. I_R





Fig. 3. Transient thermal impedance junction to case



Package Dimensions**Super TO-247**

(Dimensions in Millimeters)

